

**CD-9360 SONY Indoor/Outdoor
Day/Night Long-Range Infrared
Varifocal 540 TVL Camera**



Installation Manual

Outdoor Varifocal Hi-Res Day/Night
Infrared CCD Bullet Camera

Camera Installation

1. Camera Mounting:

Items Needed:

Screwdriver, Drill, Mounting Hardware (not included), Pencil

2. Mark the bolt holes and attach bracket to wall



3. Loosen the adjustments and position camera as desired.



Camera Installation

4. Remove back of camera housing



5. Adjust Zoom/Focus with 2 adjustment screws
6. Set Camera's higher level functions with On-Screen Display once connected.

Platinum CCTV Surveillance Solutions

CD-9360 Long Range IR CCD Camera	
Image Sensor	1/3" SONY HQ1 CCD
Number of Pixels	NTSC: 540 (H) x 491 (V)
Scanning System	15.7343Khz (H), 60 Hz (V)
Sync System	Internal Synchronization
Resolution	540 TVL
Lens	4-9mm Varifocal Lens (Ext. Adjust)
Video Output	1.0Vp-p75Ω
S/N Ratio	>52dB
Shutter Time	1/60-1/100,000 Sec.
Operation Temp.	-20°C ~ +50°C
Storage Temp.	-30°C ~ +60°C
Useable Illumination	0.015 Lux (F:2.0), 0 Lux (IR On)
Power Source	DC 12V 700mA

Installation Notes

- For Indoor or Outdoor Use
- Disassembly of camera will void warranty
- Remove protective film from lens before use
- Handle with care
- Never touch lens directly
- Clean the lens occasionally with a dry micro-fiber cloth, or plastic cleaner only – Do not use abrasive-type cleaners as they will scratch lens